

GrecoCrete® Fix 11

Normal cementitious tile adhesive

Description

GrecoCrete Fix 11 is a ready to use, polymer modified cementitious tile adhesive of class C1

Uses

GrecoCrete Fix 11 is designed for bonding of small to medium size ceramic, homogenous tiles and mosaic not bigger than 600mm x 300mm for floors and walls.

Areas of application

- Vertical and horizontal application
- Internal and external tile fixing

Typical Properties

Colour	: Grey
Density (wet)	: Approx. 1,800 kg/m ³
Tensile Adhesion Bond Strength @ 28 days (BS EN 12004-2: 2017)	: ≥ 0.5 N/mm ²
Pot life (at 30°C)	: Approx. 30 minutes
Mixing Water (For 20 kg bag)	: 4.5 - 4.7L for Grey

Coverage

Typical coverage using 6mm notched trowel is approximately 3.4kg/m²

Application

Surface Preparation

Substrate must be structurally sound, dry and clean. Cement laitence, mould release agent, curing compound, oil, grease or any loose particle which may impair bond must be removed using effective means such as sandblasting, high pressure water jetting, scabbling, grinding and etc.

For concrete slabs, must be allowed to cure fully and have a wood float finish. Steel trowel finished surfaces must be mechanically toughen before tilling work.

Pre-saturate surface with clean water prior to application of **GrecoCrete Fix 11**. Substrate should be saturated surface dry and free of surface water. Preference will be for newly plastered walls or bedded floors.

Mixing

Mechanical mixing to uniform, homogeneous consistency using a low speed drill (400 rpm) fitted with a wing profile mixing paddle is recommended.

For wall tile application, add 10% of **GreBond 260** to mixing water by weight to enhance the bonding properties.



Method of Application

Apply **GrecoCrete Fix 11** to substrate with a notched trowel for sufficient work area within the pot life. Lay tiles immediately onto the fresh adhesive and firmly fix it to ensure good contact behind the tiles.

Ant adjustment of tiles should be done within the 15 minutes after installation, beyond which the existing adhesive should be removed and a fresh coat of adhesive should be reapplied to the substrates.

Cleaning

Use water to clean tools and equipment immediately after use.

Packaging

GrecoCrete Fix 11 is available in 20kg bag.

Shelf Life

GrecoCrete Fix 11 has a shelf life of 12 months when stored in original packing in a cool and dry environment.

Health & Safety

GrecoCrete Fix 11 contains cement powder and can cause irritation to person with sensitive skin. Avoid skin and eye contact. Wear suitable protective clothing, masks and gloves while handling product.

Note:

Use the leaflet as a guide for the use of this product concerned. The information given is in accordance with the latest technical developments. However, we cannot accept responsibility for any work carried out with our materials as we have no control over the method of application used or the condition of the site involved.

Last updated by KH/MAR 2019