

GrecoCrete® Fix 88

Single component tile adhesive

Description

GrecoCrete Fix 88 is a ready to use, polymer modified cement based tile adhesive system tile adhesive of class C2.

Uses

GrecoCrete Fix 88 is designed for thin bedding adhesive for vertical and horizontal application with good sag resistance. It is ideal for top down application with general tiles.

Areas of application

- Vertical and horizontal application
- Internal and external tile fixing

Typical Properties

Colour	: Cement Grey
Density (wet)	: Approx. 1,700 kg/m ³
Tensile Adhesion	: ≥ 1.0 N/mm ² @ 28 days (Grey)
Compressive Strength @ 28 days	: ≥ 8.0 N/mm ² for Grey
Pot life (at 30°C)	: Approx. 30 minutes
Mixing Water (For 25 kg bag)	: 6 - 6.5L for Grey

Coverage

Typical coverage is 14 m²/ 25kg bag per 1mm thickness.

Application

Surface Preparation
Substrate must be structurally sound, dry and clean. Cement laitence, mould release agent, curing compound, oil, grease or any loose particle which may impair bond must be removed using effective means such as sandblasting, high pressure water jetting, scabbling, grinding and etc.
Pre-saturate surface with clean water prior to application of **GrecoCrete Fix 88**. Substrate should be saturated surface dry and free of surface water. Preference will be for newly plastered walls or bedded floors.

Mixing

Mechanical mixing to uniform, homogeneous consistency using a low speed drill (400 rpm) fitted with a wing profile mixing paddle is recommended.



Method of Application

Apply **GrecoCrete Fix 88** to substrate with a notched trowel for sufficient work area within the pot life. Lay tiles immediately onto the fresh adhesive and firmly fix it to ensure good contact behind the tiles.

Ant adjustment of tiles should be done within the 15 minutes after installation, beyond which the existing adhesive should be removed and a fresh coat of adhesive should be reapplied to the substrates.

Cleaning

Use water to clean tools and equipment immediately after use.

Packaging

GrecoCrete Fix 88 is available in 25kg bag.

Shelf Life

GrecoCrete Fix 88 has a shelf life of 12 months when stored in original packing in a cool and dry environment.

Health & Safety

GrecoCrete Fix 88 contains cement powder and can cause irritation to person with sensitive skin. Avoid skin and eye contact. Wear suitable protective clothing, masks and gloves while handling product.

Note:

Use the leaflet as a guide for the use of this product concerned. The information given is in accordance with the latest technical developments. However, we cannot accept responsibility for any work carried out with our materials as we have no control over the method of application used or the condition of the site involved.

Last updated by KH/JUNE 2022